

## **ENGEN TWO STROKE SUPER**

### **DESCRIPTION**

Engen Two Stroke Super is a superior quality, non-ash forming SAE 30 Two Stroke motor oil. It is dyed blue for ease of identification. Engen Two Stroke Super provides miscibility and fluidity characteristics meeting Grade 2 of SAE J1536 and far exceeds the API TC performance level.

### **APPLICATION**

Engen Two Stroke Super can be used in applications where the lubricant is premixed with the fuel, or by metered injection into the engine intake system at ratios up to 50:1. Always use ratio recommended by the engine manufacturer. Engen Two Stroke Super is especially formulated for use in modern air cooled two stroke petrol engines. It is suitable for use in racing and severe duty two stroke motorcycle engines as well as modern high revving chainsaws, lawnmowers, scooters and generator sets.

### **PERFORMANCE LEVEL**

API TC, SAE J1536 Grade 2

### **BENEFITS**

- Exceeds API TC
- Extended spark plug life
- Protection against spark plug fouling
- Effective lubrication at all speeds and loads
- Excellent miscibility and fluidity characteristics
- Protection against combustion chamber and exhaust port deposits

### **TYPICAL PHYSICAL CHARACTERISTICS**

SAE No.	30
Viscosity, cSt @ 40 °C	68
cSt @ 100 °C	9,6
Viscosity Index.	110
Flash Point, °C	110
Pour Point, °C	-9
Colour, Visual	Blue