

ENGEN MULTIGRADE 25W-50

DESCRIPTION

Engen Multigrade 25W-50 is a robust, cost effective, SAE 25W-50, engine crankcase oil suitable for use in older, high mileage cars, mini bus taxis, light commercial vehicles and contractor equipment where oil consumption is of concern. It provides good wear protection on starting and during warm-up. Being a SAE 25W-50 viscosity oil it gives good wear protection by providing a thicker oil film on bearing surfaces as well as better sealing of piston rings, reducing oil consumption and blow-by. It exceeds API Service Classification SG/CF-4.

APPLICATION

Engen Multigrade 25W-50 is recommended for older, naturally aspirated petrol and diesel engines of passenger cars, mini bus taxis, light commercial vehicles and contractor equipment involved in start/stop operations with short service intervals. Engen Multigrade 25W-50 should not be used in extended service applications. Always consult the manufactures operating manual to confirm the suitability of the lubricant for a particular vehicle.

PERFORMANCE LEVEL

API SG/CF-4.

BENEFITS

- Excellent protection against wear and corrosion.
- Keeps engines clean.
- Reduces oil consumption.
- Maintains optimum viscosity at all temperatures.
- Smooth engine operation.

TYPICAL PHYSICAL CHARACTERISTICS

SAE No.	25W-50
Viscosity, cSt @ 40 °C	190
cSt @100 °C	18
Viscosity Index	100
Flash point °C	230
Pour Point °C	-18
Total Base No., mgKOH/g	12
Sulphated Ash, % m/m	1,0