

# Gensaw 150

*Chain Saw Lubricant*

## Description

Gensaw 150 is a specially formulated mineral oil required to lubricate the cutting chain, cutter bar and drive gear on hand-held Chain Saws. The oil contains a tackiness additive to ensure that adequate lubricant adheres to the rubbing surfaces of this total loss system.

## Application

Gensaw 150 is recommended for all makes of hand-held chain saws including Dolar, Echo, Husqvarna, Jonsereds, McCulloch, Partner and Stihl.

**NOTE:** Engen Two Stroke Super, which is dyed green for ease of identification, is a superior quality two stroke engine oil that far exceeds the API TC performance level and is the prime recommendation for the lubrication of high revving Chain Saw engines.

## Benefits

- Excellent lubrication.
- Super adhesive and cohesive properties.

## Typical Physical Characteristics

Gensaw 150	
Viscosity, cSt @ 40 °C	150
Viscosity, cSt @ 100 °C	14,4
Flash Point, °C, min.	228
Pour Point, °C, max.	-6
Density @ 20 °C, kg/l	0,880
ISO VG	150

02.2015

*Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.*

**Engen Petroleum Ltd | Tel: 08600 36436 | Website: [www.engenoil.com](http://www.engenoil.com) | Email: [1call@engenoil.com](mailto:1call@engenoil.com)**